



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/716,367	11/18/2003	Joseph J. Lacey	390086.95207	6672
28382	7590	05/02/2005		
QUARLES & BRADY LLP 411 E. WISCONSIN AVENUE SUITE 2040 MILWAUKEE, WI 53202-4497				
EXAMINER ROSENBERGER, FREDERICK F				
ART UNIT		PAPER NUMBER		
2878				

DATE MAILED: 05/02/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary

Application No.

10/716,367

Applicant(s)

LACEY ET AL.

Examiner

Frederick F. Rosenberger

Art Unit

2878

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 25 February 2005.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-20 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-3 and 5-20 is/are rejected.
- 7) ☒ Claim(s) 4 is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 11/18/03 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
 - ☐ Certified copies of the priority documents have been received in Application No. _____.
 - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date <u>11/18/03</u> | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Response to Amendment

1. Applicant's amendment, dated February 24th, 2005, has been received and entered.

Priority

2. As the specification has been amended to include a specific reference to the prior application and the relationship between applications, the claim for domestic priority under 35 U.S.C. 120 to nonprovisional application 10/064609, filed July 30th, 2002, is acknowledged.

Information Disclosure Statement

3. The Information Disclosure Statement (IDS) received with the filing of this application on November 18th, 2003 is acceptable. The objection cited in the previous Office action, dated November 24th, 2004, is hereby withdrawn. The failure to initial all cited references on the IDS was an oversight. As such, an amended IDS has been included with this Office action showing the appropriate markings.

Response to Arguments

4. Applicant's arguments with respect to claims 1-20 have been considered but are moot in view of the new ground(s) of rejection.

5. In response to applicant's request for a translation of the Yoshioka reference (Japanese publication # 61-201182), a translation of said reference has been included with this Office action.

Claim Rejections - 35 USC § 103

6. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.

7. Claims 1-3, and 10 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yoshioka (Japanese Publication # 61-201182A) in view of Lacey (US Patent # 6,459,757).

Yoshioka discloses a detector assembly for use in a computed tomography scanner, the detector assembly comprising:

A detector array **10** (Figures 1 and 2);

A temperature sensor **S3** coupled to the center of the detector array **10** and temperature sensors **S1** and **S2** coupled to the opposing ends of the detector array **10**;

A heater **H3** coupled to a center portion of the detector array **10** and heating elements **H1** and **H2** coupled to the opposing ends of the detector array **10**;

And a controller device **11a, 11b, 11c** electrically coupled to the temperature sensors to receive an actual temperature signal, the controller device

Art Unit: 2878

comparing the actual temperature signal to a set point and driving the heater to maintain the heaters **H1-H3** to maintain the actual temperature substantially at set point, thus providing a uniform temperature profile along the array (Figure 3 and page 6 of the translation, lines 3-6).

Yoshioka is silent with regards to the use of thermoelectric coolers at the opposing ends of the detector array, instead opting for surface heaters with no definition of variations.

However, it is well known in the art that thermoelectric coolers are capable of being used in place of standard heaters as a heating/cooling element. For example, Lacey points out that heaters in a temperature control apparatus for an X-ray detector can take the form of thermoelectric coolers (column 5, lines 14-16). Further, Lacey discloses that the use of thermoelectric coolers in such a temperature control setup is desirable since the added functionality of the thermoelectric cooler allows for cooling the detector array when ambient temperatures exceed allowable module operating ranges (column 5, lines 20-27).

Thus, it would have been obvious for a person of ordinary skill in the art to change at least one of the outlying heaters **H1** and **H2** of Yoshioka to thermoelectric coolers, along with the appropriate controller modifications, to enable cooling of the detector array when ambient temperatures are too high, as taught by Lacey.

8. Claims 5, 6, 12, and 13 are rejected under 35 U.S.C. 103(a) as being unpatentable Yoshioka and Lacey, as applied to claims 1 and 10 above, and further in

Art Unit: 2878

view of internet document entitled "Designing with Thermoelectric Coolers" (hereinafter referred to as Design Guide) and "Thermoelectric Reference Guide-Heat Sink Considerations" (hereinafter referred to as Ferrotec).

Yoshioka and Lacey disclose all the limitations of the parent claims 1 and 10, as described above. However, the combination of Yoshioka and Lacey are silent with regards to the method for heat dissipation from the thermoelectric cooler.

It is well known in the art that the use of a thermoelectric cooler requires the use of some form of heat dissipation method, whether natural or active heat dissipation. As Design Guide points (page 3, entitled "What is the required balance system needed to enable a TEC?"), without a suitable heat dissipation method to remove heat from the hot side, the thermoelectric cooler will eventually overheat and fail. Acceptable heat dissipation methods include natural convection extruded fins (i.e. traditional heat sink), forced convection fins stack (i.e. fan directing air at a heat sink), or a fluid cooling heat exchanger. Ferrotec also points out that the particular selection of an appropriate heat dissipation is dependent upon the particular application. Lower power applications require only a natural convection heat sink (section 5.2.1) while higher power applications (i.e. those that require more heat removal) require at least forced convection heat sinks (section 5.2.2).

Thus, it would have been obvious to a person having ordinary skill in the art at the time the invention was made to apply heat dissipation methods, either passive heat sinks via natural convection or active heat sinks through directed fans, for the

Art Unit: 2878

thermoelectric coolers, to prevent failure of the thermoelectric coolers, as taught by Design Guide and Ferrotec.

9. Claims 7, 8, and 16-20 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yoshioka, Lacey, Design Guide and Ferrotec, as applied to claim 5 above, and further in view of Snyder et al. (US Patent # 6,249,563).

The combination of Yoshioka, Lacey, Design Guide, and Ferrotec discloses all of the limitations of parent claim 5, as described above, and most of the limitations of claims 16-20. However, the combination is silent with regards to rails being coupled to opposing sides of the detector array with a conductive insert coupled to one of the rails for transferring heat along the rail.

Snyder et al. teach a temperature control method for an X-ray detector employing a pair of rails **42a**, **42b** (Figure 3) mounted on opposing sides of a detector array **39** with conductive inserts **46** along the length of the rails enabled for transferring heat along the length of the array (column 5, lines 3-9). As Snyder et al. illustrate, such a configuration enables the rapid transfer of heat from detector locations at different temperatures, thereby encouraging an isothermal condition among the detector array elements (column 5, lines 12-17).

Thus, it would have been obvious to a person having ordinary skill in the art to modify the combination of Yoshioka, Lacey, Design Guide, and Ferrotec, to include a pair of rails with conductive inserts to enhance heat distribution along the entire length

Art Unit: 2878

of the detector array and assist in the maintenance of a uniform temperature profile, as taught by Snyder et al.

With regards to claim 8, although Snyder et al. teach a conductive insert which is a fluid filled heat pipe, the particular selection of the conductive insert material is an obvious matter of design choice since applicant has not disclosed that the particular material selection solves any stated problem or is for any particular purpose and it appears that the invention would perform equally well with a fluid filled heat pipe with high thermal conductivity, as proposed by Snyder et al.

With regards to claim 20, Yoshioka demonstrates that the temperature in the center of the detector (Figure 3 – location III) is higher than it would be at the extreme ends of the detector array (Figure 3, to the left of location I and to the right of location II).

10. Claims 9 and 14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yoshioka and Lacey, as applied to claims 1 and 10 above, and further in view of Sasaki et al. (US Patent # 6,411,672).

The combination of Yoshioka and Lacey discloses all of the limitations of parent claims 1 and 10, as described above. However, the combination is silent with regards to providing an insulating cover for housing the detector array from ambient thermal variations.

Sasaki et al. teach a radiation detector for X-ray CT applications wherein the detector array 25 (Figure 2) is encased in a case 17 with insulation 21. The insulation is configured such that it is in thermal communication with all edges of the detector array

Art Unit: 2878

through the working fluid except for a window **16** (Figures 3) on the top of the detector array. Such a setup enables a uniform internal temperature with high thermal conductivity in the interior of the detector assembly while enabling high insulation with respect to the exterior of the detector assembly (column 3, lines 39-45).

Thus, it would have been obvious for a person having ordinary skill in the art to modify Yoshioka and Lacey to include an insulating cover for housing the detector array from ambient conditions so as to better maintain an internal isothermal condition, as taught by Sasaki et al.

11. Claims 11 and 15 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yoshioka and Lacey, as applied to claim 10 above, and further in view of Snyder et al. (US Patent # 6,249,563).

The combination of Yoshioka and Lacey discloses all of the limitations of parent claim 10, as described above. However, the combination is silent with regards to a heat conductive material coupled along the length of the detector array for transferring heat.

Snyder et al. teach a temperature control method for an X-ray detector employing a pair of rails **42a**, **42b** (Figure 3) mounted on opposing sides of a detector array **39** with conductive inserts **46** as heat conductive material coupled along the length of the rails enabled for transferring heat along the length of the array (column 5, lines 3-9). As Snyder et al. illustrate, such a configuration enables the rapid transfer of heat from

Art Unit: 2878

detector locations at different temperatures, thereby encouraging an isothermal condition among the detector array elements (column 5, lines 12-17).

Thus, it would have been obvious to a person having ordinary skill in the art to modify the combination of Yoshioka, Lacey, Design Guide, and Ferrotec, to include a pair of rails with conductive inserts as heat conductive material to enhance heat distribution along the entire length of the detector array and assist in the maintenance of a uniform temperature profile, as taught by Snyder et al.

Allowable Subject Matter

12. Claim 4 is objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

13. The following is a statement of reasons for the indication of allowable subject matter:

Claim 4, when incorporating the limitations of parent claims 1 and 3, is directed towards a detector assembly for use in a CT scanner, wherein the detector assembly comprises a detector array with a thermoelectric cooler, a centrally located heater coupled to the array, an appropriately located temperature sensor coupled to the array, and a controller for controlling the temperature profile of the detector array to have a parabolic shape.

While aspects of the invention can be found in the prior art, the temperature profile having a parabolic shape is a unique feature of the present invention. Yoshioka discloses a parabolic temperature profile (see Figure 9), but cites this as a negative limitation of prior art temperature stabilization systems (page 4 of the translation, lines 4-15). In fact, the prior art as a whole emphasizes attainment of a uniform temperature profile for the detector profile. As such, applicant's disclosure provides a novel and nonobvious improvement over the prior art. Accordingly, the claim 4 would be allowable.

Conclusion

14. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Frederick F. Rosenberger whose telephone number is 571-272-6107. The examiner can normally be reached on Monday-Friday 7:30 AM - 4:30 PM.

15. If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David Porta can be reached on 571-272-2444. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Art Unit: 2878

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Frederick F. Rosenberger
Patent Examiner
GAU 2878



DAVID PORTA
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2800